

ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):	entifier(s): Dominus 20										
Indirect heating functionality:				yes							
Direct heat output:	9,6										
Indirect heat output:	10,9										
Fuel	Preferred fuel (only one):	Other suitable fuel(s):	η _s [%]:	Space heating emissions at nominal heat output (*)				Space heating emissions at minimum heat output (*) (**)			
				PM	OGC	CO	NO _x	PM	OGC	СО	NO _x
				mg/Nm ³ (13%O ₂)			mg/Nm3 (13%O2)				
Wood logs with moisture content ≤ 25 %	yes	no	75,4	25	67	1221	73	-	-	-	-
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit	Item Symb	ool Value	Unit
Heat output	l.			Useful efficiency (NCV as rece	ived)	
Nominal heat output	P _{nom}	20,5	kW	Useful efficiency at nominal heat output $\eta_{\text{th,no}}$	_{om} 85,4	%
Minimum heat output (indicative)	P _{min}	-	kW	Useful efficiency at minimum heat output η _{th,n} (indicative)	nin -	%
Auxiliary elettricity consun	nption			Type of heat output/room ten	nperature con	trol (select
At nominal heat output	el _{max}	-	kW	single stage heat output, no retemperature control	oom no	
At minimum heat output	el _{min}	-	kW	two or more manual stages, room temperature control	no no	
In standby mode	el _{SB}	-	kW	with mechanic thermostat retemperature control	oom no	
Permanent pilot flame pow	er require	ement		with eletronic room tempear control	ture no	
Pilot flame power requirement (if applicable)	P _{pilot}	n.p.	kW	with eletronic room tempear control plus day timer	ture no	
requirement (ii applicable)				with eletronic room tempear control plus week timer	ture no	
				Other control options (multiple	e selections po	ossible)
				room temperature control, presence detector	with no	
				room temperature control, with c window detection	ppen no	
				with distance control option	no	
Contact details		Name a	nd addre	of the manufacturer or its authorised	representative	9
+39 0824948016 +39 0824 948499			(struzioni Tecniche Meccaniche S.r.l.		

(*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO_x = nitrogen oxides (**) Only required if correction factors F(2) or F(3) are applied

Via Cese Nove - Zona Industriale, snc - 82030 San Salvatore Telesino (BN) - IT

Note:

F(2) 0 F(3) 0

mp@cmt-italia.it

www.ctm-italia.it

Technical report ref. 2004270

Approved by

Maurizio Lorenzon

Lab manager

Lab manager