

## ECODESIGN REQUIREMENTS FOR SOLID FUEL LOCAL SPACE HEATERS ACCORDING TO COMMISSION REGULATION (EU) 2015/1185 IMPLEMENTING DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL

Model Identifier(s):	(s): Superior 30										
Indirect heating functionality:				yes							
Direct heat output:	10,3										
Indirect heat output:	16,0										
Fuel	Preferred fuel (only one):	Other suitable fuel(s):	η <sub>s</sub> [%]:	Space heating emissions at nominal heat output (*)				Space heating emissions at minimum heat output (*) (**)			
				PM	OGC	CO	NO <sub>x</sub>	PM	OGC	CO	$NO_x$
				mg/Nm <sup>3</sup> (13%O <sub>2</sub> )			mg/Nm3 (13%O2)				
Wood logs with moisture content ≤ 25 %	yes	no	74,4	28	64	1156	80	-	-	-	-
Compressed wood with moisture content < 12 %	no	no									
Other woody biomass	no	no									
Non-woody biomass	no	no									
Anthracite and dry steam coal	no	no									
Hard coke	no	no									
Low temperature coke	no	no									
Bituminus coal	no	no									
Lignite briquettes	no	no									
Peat briquettes	no	no									
Blended fossil fuel briquettes	no	no									
Other fossil fuel	no	no									
Blended biomass and fossil fuel briquettes	no	no									
Other blend of biomass and solid fuel	no	no									



## Characteristics when operating with the preferred fuel only:

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Heat output	1	1		Useful efficiency (NCV a	s received	)	
Nominal heat output	P <sub>nom</sub>	26,4	kW	Useful efficiency at nominal heat output	$\eta_{\text{th,nom}}$	84,4	%
Minimum heat output (indicative)	P <sub>min</sub>	-	kW	Useful efficiency at minimum heat output (indicative)	$\eta_{th,min}$	-	%
Auxiliary elettricity consun	nption			Type of heat output/roo	om tempera	ature cont	rol (select
At nominal heat output	el <sub>max</sub>	-	kW	single stage heat output temperature control	single stage heat output, no room temperature control		
At minimum heat output	el <sub>min</sub>	-	kW		two or more manual stages, no room temperature control		
In standby mode	el <sub>SB</sub>	-	kW	with mechanic thermostemperature control	with mechanic thermostat room temperature control		
Permanent pilot flame pow	er require	ement		with eletronic room to control	empearture	no	
Pilot flame power requirement (if applicable)			with eletronic room to control plus day timer	empearture	no		
Tequirement (ii applicable)				with eletronic room to control plus week timer	empearture	no	
				Other control options (n	nultiple sel	ections po	ssible)
				room temperature cor presence detector	ntrol, with	no	
				room temperature control window detection	, with open	no	
				with distance control option	on	no	
Contact details		Name a	nd address	of the manufacturer or its auth	orised repr	esentative	•
+39 0824948016							
+39 N824 948499			Cos	struzioni Tecniche Meccaniche	Srl		

+39 0824 948499 Costruzioni Tecniche Meccaniche S.r.l. mp@cmt-italia.it Via Cese Nove - Zona Industriale, snc - 82030 San Salvatore Telesino (BN) - IT www.ctm-italia.it

(\*) PM = particulate matter, OGC = organic gaseous compounds, CO = carbon monoxide, NO<sub>x</sub> = nitrogen oxides

(\*\*) Only required if correction factors F(2) or F(3) are applied

0

Note:

F(2) 0 F(3)

Technical report ref. 2004696

> Approved by Maurizio Lorenzon Lab manager